



Department of Procurement Services

160 Glenn Rogers Sr. Street · Room 126 · Memphis, TN 38112 · (901) 416-5376

April 14, 2025

Addendum #II: IFB04252025MES – CNC Forklift II

Dear Bidders:

This Addendum forms a part of the Contract Documents. The Contractor shall acknowledge receipt of this Addendum on the Bid Form. Failure to do so may subject the Bidder to disqualification. Addendum II shall be located on the MSCS Procurement website, [Procurement \(scsk12.org\)](http://Procurement(scsk12.org)). For your convenience, the Addendum II is attached.

Item #1 – PART IV: SCOPE OF WORK SPECIFICATION

The original language stated the following:

Mfg. Standard for Destination ANSI
UL Type EE Rated UL E Rated (Standard)
Battery Voltage 24
Mast Type TT
Straddle Standard
Lift Height 210"/5330mm
Collapsed Height 95"/2415mm
Extended Height 296"/7520mm
Lift/Lower Cutout Programmable Lift/Lower Cutout
Hydraulic Performance Package Standard Lower with Regenerative Lowering Lift Speed Standard
Power Source Type Standard Lead Acid Battery
Platform Step Height STD 8.75"/225mm Step Platform
Environmental Package Freezer Conditioning
Cold Conditioning Oil 50% Freezer Hydraulic Oil Mix
Operator Compartment Depth 27"/685mm
Operator Compartment Height 78"/1980mm
Operator Compartment Width 48"/1220mm
Overhead Guard Options Steel Slats
Overhead Guard Extensions with LED Pick Bay Lights 42"/1065mm
Keyless On/Off Switch Key Switch
Fork Type 2"x4"/50mm x 100mm Solid Forks
Fork Length 42"/1065mm
Adjustable Fork Spread 24" - 30"/610mm - 762mm

Outrigger Outside Dimension 48"/1220mm
Battery Compartment B Compartment
Battery Spacer / Max. Batt Size B58 14.06" x 36.25" x 31" / 357mm x 921mm x 787mm
Battery Connector Type SB350
Battery Connector Color Gray
Operator Controls Adjustable Height Power Unit Facing
Capacitive Touchscreen Display
Display Location Right Side - Power Unit Facing
Display Navigation Knob Yes
Floor Mat Ribbed Mat with Foam Backing
Pallet Grab Manual - 1.5"/40mm Wide Stringer
Body Harness Full Body Harness L/XL
Tether Retractable Tether
Tether Location Alternative Tether Attachment Locations
Upper Visibility Window Wire Mesh Screen
Middle Visibility Window Wire Mesh
Center Floor Visibility Window Yes
Side Floor Slot Visibility Windows Yes
Two Operator Fans, LED Dome and Work Light Package Yes
Side Gates with Integrated Bungee Cord Cantilever
Drive Tire Poly Black Smooth
Load Wheel Compound -302
Rear View Mirror Power Unit Facing Rearview Mirrors 2 Mirror
Plastic
LED Spotlights Overhead Guard Mounted LED
LED Flashing Lights Amber LED
Audible Travel Alarm Smart Travel Alarm (Power Unit First)
Service Panel Yes
Upper Side Mount Work Assist Option 1 Clip Board
Upper Side Mount Work Assist Option 3 Rearview Mirror -Plastic
Upper Side Mount Work Assist Option 4 Rearview Mirror -Plastic
OnTrac™ Anti-Slip Traction Control OnTrac™ Anti-Slip Traction Control
Label & Decal Language US English
Warranties:
Standard Warranty Standard - 1 Year / Unlimited Hours

The successful bidder will deliver to 3176 Jackson Avenue, Memphis TN, 38112.

All vendors must present a demo to be used in our warehouse at 3176 Jackson Avenue, Memphis TN, 38112 prior to bid closing for approval of the unit to qualify for the bid.

Please contact Quinterion Mitchell to set up your demo at 901-827-6525.

No installation is required. This bid is for equipment only.

The **revised** language reads as follows:

3,200 lb. Capacity, 36 Volt, Narrow-Aisle Reach Truck

Mfg. Standard for Destination	ANSI
Lift Height	210"/5330mm
Collapsed Height	95"/2415mm
Lift/Lower Cutout	Programmable Lift/Lower Cutout
Alternate Power Source	Standard Lead Acid Battery
Overhead Guard Type	Flat Overhead Guard
Overhead Guard Height	95"/2415mm
3rd Post On Overhead Guard	3rd Post - Standard Mast
Environmental Package	Freezer Conditioning
Cold Conditioning Oil	50% Freezer Hydraulic Oil Mix
Side shifter	2" / 50mm
Hydraulic Lift System	AC Regen Hydraulic System
Reach Extension	53"/1345mm
Fork Type	Partial Tapered Forks
Fork Length	42"/1065mm
Fork Spread	27"/685mm
Load Backrest Width	32"/815mm
Steering Option	Forward Steering
Mast Guard Options	Screen Mast Guard
Steer Tiller Option	Standard 4 1/8" Radius 105mm Radius
Drive Tire Options	Heavy-Duty Black Smooth -364
Load Wheel Size	5" x 2.9" / 125mm x 75mm
Load Wheel Compound	-302
Outtrigger Option	Tapered Outriggers
Outtrigger OD Dimension	48"/1220mm
Outtrigger ID Dimension	40"/1015mm
Front Work lights	Overhead Guard Mounted
LED Flashing Light	LED Amber Flashing Light
Travel Alarm	Smart (Reverse-PUF)
Rear View Mirror	Plastic Mirror on 3rd Post
Language For Decals	US English
Battery and Charger	Need
Warranties:	
Warranty	Standard - One Year/Unlimited Hours

The successful bidder will deliver to 3176 Jackson Avenue, Memphis TN, 38112.

All vendors must present a demo to be used in our warehouse at 3176 Jackson Avenue, Memphis TN, 38112 prior to bid closing for approval of the unit to qualify for the bid.

Please contact Quinterion Mitchell to set up your demo at 901-827-6525.

No installation is required. This bid is for equipment only.

Thank you,
Procurement Services